# BG-R201消泡剂 **Defoamer**

## 特点/Characteristic:

该产品系脂肪烃、乳化剂及无机物的混合物,属非硅酮类消泡剂。

本产品是一种液体广谱消泡剂。专用于水性涂料、水性油墨及胶乳粘合剂体系。

The product is non-silicone and wide-ranging liquid defoamer that the mixture of fatty hydrocarbon, emulsifier

It is suitable for water-base coating .Water-base printing ink and latex adhesive system.

#### 用途/Uses:

BG-R201对各种合成乳液体系均有效。具有优异的持久性而不会产生表面缺陷或影响漆膜外观。可在乳胶漆制造过 程中任一阶段加入。

建议用量为0.2~0.3%

BG-R201 is effective to all kinds of synthetic emulsion system and present superior constancy while causing no surface flaw or negative impact on the appearance of paint film . The product is added in any stage of manufacturing latex paint.
The recommended dosage is 0.2–0.3%.

#### 技术指标/Technical index:

外现	乳白至浅黄不透明液体	含水量%	0~0.3
Appearance	Cream-light yellow liquid	Moisture%	
密度 Density 20℃,g/cm²	0.84 ~ 0.89	活性物质% Active substance%	100
粘度	500 ~ 1200	离子特性	非离子
Viscosity 25℃, mPa∙S		lonic characteristic	Non-lonic

### 注意事項/Note:

性质不受霜冻影响。本产品宜贮存在10~35℃之间。如受冻,可室温下融化,绝不可直接加热,使用前应搅拌。 The frost not affect to the product property .BG-R201 store in lo-35℃ .If the frozen condition the product can melting in rt ,but not can direct heating .lt ought to stirr before use.