

UV色精系列 UV DYE STAIN

UV色精是一种用特殊的UV单体溶解的染料，与大多UV树脂及单体的相溶性非常优异，因此可广泛适用于光固化油墨、光固化木器涂料、光固化真空喷涂、光固化工业涂料等领域。产品具有色浓度高、颜料鲜艳、色彩艳丽、分散性好、透明度好的特点。此系列色精含UV单体，所以加入UV漆后，不会明显降低粘度。

UV colorant is a kind of dye dissolved by special UV monomer. It has excellent solubility with most UV resins and monomers, so it can be widely used in the fields of UV curing ink, UV curing wood coatings, UV curing vacuum spraying, UV curing industrial coatings, etc. The product has the characteristics of high color concentration, bright color, brilliant color, good dispersion and good transparency. This series contains UV monomer, so adding UV paint will not significantly reduce viscosity.

使用方法

- 使用时直接加在UV漆里，搅拌均匀，即可使用

注意事项

- 此系列色精含UV单体，请测试与体系的相溶性

贮存

- 避光，贮存于阴凉、避光干燥通风处

包装规格

- 25kg/5kg

USAGE METHOD

- When using, it is directly added to the UV paint and stirred evenly, then it can be used.

MATTERS NEEDING ATTENTION

- This series contains UV monomer, please test the compatibility with the system

STORAGE

- Store in a cool, dark, dry and ventilated place

PACKING SPECIFICATION

- 25kg/5kg

基础参数 BASIC PARAMETERS

产品编号 Product No.	产品名称 Product name	颜料索引号 C.I.NO	色相 Colour	颜料含量 Pigment%	耐光性 Light fastness	耐热性 Heat resistance	耐酸 Acid resistance	耐碱 Alkali resistance
UV-20	UV专用黄色精 YELLOW	溶剂黄21 Solvent yellow 21		25	3-4	130-150	B	B
UV-06	UV专用红色精 RED	溶剂红122 Solvent Red 122		24	4-5	140-160	A	A
UV-04	UV专用紫红色精 RED	溶剂红8 Solvent Red 8		24	4-5	140-160	A	A
UV-56	UV专用纯黑色精 BLACK	溶剂黑29 Solvent black 29		25	4-5	140-160	A	A
UV-34	UV专用蓝黑精 BLACK	溶剂黑34 Solvent black 34		25	4-5	140-160	A	A
UV-27	UV专用红口黑色精 BLACK	溶剂黑27 Solvent black 27		25	4-5	140-160	A	A