

仿古油

ANTIQUUE OIL

本产品可作为工程防腐涂料，同时又是一种特殊着色剂。其颜色为棕褐色，类似于格丽斯中常用的黄棕仿古色。

This product can be used as engineering anti-corrosion coatings, it is also a special stain. Its color is brown, similar to the Glaze used in yellow brown archaize color.

产品特性

- 可代替色精做为底色使用。
- 加在格丽斯中可增加格丽斯的着色力。
- 可避免PE底漆与格丽斯附着不好的情况。

注意事项及包装规格

- 注意出现吐油情况。擦木纹时应注意保持环境清洁，否则影响油漆附着力。
- 包装规格：3.5kg/1kg

PRODUCT CHARACTERISTICS

- Can be used instead of color as a background
- Plus in the Glaze can increase Glaze color strength;
- Can avoid PE primer and Glaze attached to the bad situation.

PRECAUTIONS AND PACKING SPECIFICATIONS

- Attention to the phenomenon of oil spit. Wipe the grain should pay attention to keep the environment clean, otherwise affect the paint adhesion.
- Packing specification : 3.5kg/1kg

特殊效果辅助材料 SPECIAL EFFECT AUXILIARY MATERIALS

产品编号 Product No.	产品名称 Product name	规格 Specifications	性能特点 properties
FC-701	白色灰尘漆 White dust paint	18kg	适用于美式家具沟槽、破坏处做旧做仿古效果，达到灰尘堆积或发霉效果，可加格丽斯调色
FC-777	灰尘漆稀释剂 Dust paint thinner	13kg	It is suitable for American style furniture groove and damaged place to make antique effect, to achieve the effect of dust accumulation or mildew, and it can be added with Grice color.
GCB-702*	沟槽宝主剂 Gougoubao main agent	4kg/20kg	可加入知木公同T-703、T-712、T-719、T721色浆调色，干速快，打磨性好，可以打磨的木纹着色剂
GCB-777*	沟槽宝稀释剂 Gougoubao diluent	13kg	It can be added with zhimugong t-703, t-712, t-719, t721 color paste for color matching. It has fast drying speed, good grindability and can be grinded.
FGY-700	仿古油 Antique oil	1kg	用于素色修整，可按照1:9配仿古油稀释剂开稀使用，直接在底材修色，也可将仿古油加入易施宝里，提高产品的渗透性
FGY-777	仿古油稀释剂 Antique oil diluent	13kg	For plain color finishing, it can be thinned according to the ratio of 1:9 with antique oil diluent. It can be directly used for color finishing on the base material, or it can be added into easybury to improve the permeability of the product.
SX-700	水性修色基料 Water based color base	16kg	可加水油两用色精修色，干速快，好施工产品附着力优异
SX-700A	水性修色基料 Water based color base	16kg	可加水油两用色精修色，干速快，可针对UV底漆的水性修色

备注：带的产品为公司重点推荐的产品 Note: the products with are the products recommended by the company.

施工工艺 CONSTRUCTION TECHNOLOGY

沟槽宝使用案例 Use case of gougoubao

工序 procedure	材料品牌编号名称 Material brand no. Name	施工方法详细说明 Construction method	施工要点 Main points of construction
白坯处理 Blank treatment	贴木皮或实木如橡木或黑胡桃 A veneer or solid wood, such as oak or black walnut.	清洗胶渍等 Cleaning glue stains, etc.	保证工件表面干净，无污渍 Ensure the surface of the workpiece is clean and free of stains
打磨 Polish	320#砂纸 320# sandpaper	手磨或机磨 Hand or machine grinding	去毛刺，木刺，去污迹、顺木纹打磨平整、光滑 Deburring, wood pricking, stain removal, and wood grain polishing are smooth and smooth.
沟槽宝(黑棕) Gougoubao (black brown)	加沟槽宝稀释剂，高成合适的粘度 Add gorgeous color essence	喷涂 Spray	均匀喷涂1个半“+”字，40分钟后打磨 Spray 1 and a half "+" words evenly, and polish after 40 minutes
打磨 Polish	砂纸320# 320# sandpaper	手磨 Hand grinding	顺木纹打磨，轻砂 Polish along wood grain, light sand
PU底漆 Pu primer	喷涂，加固剂稀释剂调配好 Spray, add curing agent diluent and mix well	喷涂 Spray	均匀喷涂两个“+”字 Spray two "+" words evenly
打磨 Polish	砂纸320# 320# sandpaper	手磨 Hand grinding	顺木纹打磨，轻砂 Polish along wood grain, light sand
PU底漆 Pu primer	喷涂，加固剂稀释剂调配好 Spray, add curing agent diluent and mix well	喷涂 Spray	均匀喷涂两个“+”字 Spray two "+" words evenly
打磨 Polish	砂纸320# 600# 320# 600# sandpaper	手磨 Hand grinding	顺木纹打磨，轻砂 Polish along wood grain, light sand
修色 Color fixing	修色油加色精 Toner oil and toner	修色 Color fixing	均匀修到样板颜色 Even trim to sample color
轻砂 Light sand	600#、1000#	轻磨 Light grinding	喷涂面漆两个“+”字，24小时后包装 Spray two "+" words on the top coat, 24 hours later

工艺特性：施工简单，完美体现木纹，导管做深，表面较为干净，层次感强
Process characteristics: simple construction, perfect reflection of wood grain, deep conduit, clean surface, strong sense of hierarchy