

13 特透粉 Transparent powder

1. 产品简介 Product Profile

清远市鑫辉化工有限公司VGS系列特透粉是目前市场中各种等涂料产品的底漆面漆用新型的填充料。其产品特点，可满足涂料对填充料的透明性、硬度、打磨性等各方面的较高要求。是一种易分散、粒径小、易打磨的高透明粉末。

VGS series transparency powder is currently a new type of filling material for primer and top coat of coating products. Its unique high transparency, high hardness can meet the relatively high requirement for coating transparency, hardness of filling material, it is a kind of easy to dispersing, small particle size, easy to burnish, scratch resistant high transparent powder.

2. 物化数据 Physical and chemical data

产品型号	细度	干燥损失 (105°C/2h)	吸油值	平均粒径 (Malvern)	pH值 (5%水悬浮液)	结晶水 含量	比重	白度
Product No.	Fineness	Loss on drying	Oil absorption	Particle size (Malvern)	pH wert (5% in water)	Crystal water content	Specific gravity	Whiteness
	目	%, ≤	g/100g	d_{50} , μm		%, ≤	g/cm ³	%, ≥
VGS-338	2000	5.0	28 ± 5	8.0-8.5	7.0-8.0	20	2.65	93
VGS-368	3000	5.0	28 ± 5	7.0-8.0	7.0-8.0	20	2.65	93
VGS-389	5000	5.0	30 ± 5	5.0-6.0	7.0-8.0	20	2.65	93

3. 产品特性 Product features

- ◆ 易分散 easy dispersion
- ◆ 优异的透明性 excellent transparency
- ◆ 优异的打磨性 excellent burnish

4. 应用领域 Application areas

主要应用于各种涂料透明底漆中
mainly used in all kinds of clear base coat

5. 包装 Packing

净重25kg/包 net weight 25 kg/bag

6. 储存 Storage

产品开包后，未用完的应把袋口扎紧，以防受潮和被沾污。

Once opened, the bag must be tightened in order to prevent the rest of the product from damp and pollution.

