

## Product Data Sheet 产品信息

### Greesol DF40

#### 消泡剂

#### DESCRIPTION and KEY PERFORMANCE PROPERTIES / 概述

Greesol DF40 是一支聚合物复合类水基消泡剂，为微黄色不透明液体，运用微泡溶解技术，具有极好脱泡性和相溶性。不分层，具有持久消泡性，比较容易加入到配方体系中，可以与聚醚改性硅氧烷类消泡剂协同消泡。

#### SALES SPECIFICATIONS / 技术指标

Solid content 非挥发物质含量	100%
Style 类别	聚合物
Appearance 外观	微黄色不透明液体
Specific gravity 比重, 25°C	0.86
Viscosity(25°C)粘度 CPS	200-500

以上数据视为典型值，而非特指。

#### APPLICATION GUIDELINES / 应用

水性工业涂料（中，哑光体系），水性油墨，水性胶粘剂

#### USE/使用

Greesol DF40添加剂添加量一般为整体配方重量的0.1~1%。生产前应进行全面测试，以确保获得预期的性能。使用前建议搅拌均匀，保证最大使用效果。

#### PACKING AND SAVE / 包装与储存

在4°C（39.2°F）和50°C（122°F）之间保存，Greesol DF40自生产之日起保质期为12个月。Greesol DF40 装于 25 公斤/200公斤（净重）的PE桶内。

The information contained in this document is based on trials carried out by our Technical centres and data selected from literature, but shall in no event be held or constitute or imply any warranty or undertaking, expressed or implied, or commitment on our part. Our formal specifications define the limit of our commitment. No liability whatsoever can be accepted by CHEM ADDITIVE with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.