

浙江丰虹新材料股份有限公司

ZHEJIANG FENGHONGNEW MATERIALS CO.,LTD

EFFICIENT MUD SOIL FHDF-25

GENERAL INFORMATION

FHDF-25 is a kind of modified bentonite, easily dispersing in water and having high mud-making capacity.

APPLICATION

FHDF-25 can be used in blind drilling field with water.

PROPERTY

High mud-making capacity

Low solid content with high viscosity

Low sand content

High suspension property

High unctuosity property

Low filter cake thickness

Low filter loss

LEVELS OF USE

Typical levels are between 2-3% FHDF-25 based on total system weight.

THE MAIN PRODUCT QUALITY INDEX

TYPE	FHD-130DK
COLOR/FORM	yellow, finely powder
MOISTURE, %	≤12.0
FINENESS (-200mesh)	≥85
Φ600 value, Pa.s	≥30
Filter loss, ml	≤15.0

Address: Zhejiang Province Anji county Economic Development Zone Postcode: 313300

Cs: 400-015-9989 Fax: (86) 0572-5028640



浙江丰虹新材料股份有限公司

ZHEJIANG FENGHONGNEW MATERIALS CO.,LTD

PACKAGE AND STORAGE RECOMMENDATIONS

Package: double packing, the inner kraft paper bag, outer polyethylene film bag.

Store in a cool, dry location

FHDF-25 has a shelf life of 12 months form date of manufacture.

Address: Zhejiang Province Anji county Economic Development Zone Postcode: 313300

Cs: 400-015-9989 Fax: (86) 0572-5028640
Website: http://www.zjfenghong.com E-mail: organoclay@zjfhht.com