ADH931 产品说明书
Technical Data Sheet

产品名称 Product Name：2 官能度附着力聚酯丙烯酸酯低聚物
2 Functional Adhesion Polyester Acry

产品代号 Product Code：ADH931

性能指标：Performance indicators:

外 观 Appearance （25℃）：	粘稠透明液体 viscous transparent liquid
色 数 Chromatic number（Fe-Co）：	≤2#
粘 度 Viscosity：	550-850 cps（25℃）
官能度 Functional：	2
固含 Solid content：	≥98%
酸价 Acid value：	<5
包装规格 Packing：	20kg/200kg

特性 Features：

➢ 对各类竹木基材及金属陶瓷等附着力好；Good adhesion to all kinds of bamboo and wood substrates and cermet;

➢ 粘度低，流平性好，对竹木基材润湿性能好；Low viscosity, good leveling property, good wetting on bamboo and wood substrate;

➢ 涂膜柔韧性好，固化速度快，对粉料润湿好；Good film flexibility, fast curing speed, good wetting of powder;

➢ 抗黄变性能优异，重涂性能好。Excellent anti-yellowing performance, good repainting performance.

用 途 Application：

主要用于家具无溶剂喷涂底漆或者辊涂附着力底漆。
Mainly used for furniture solvent-free spraying primer or roller coating adhesion primer.

参考配方：

ADH931--------------------------92,

滑石粉 French chalk------------8,

光敏剂 photosensitizer---------6.

贮 存 Storage:

本品须远离阳光及热源；This product should be away from sunlight and heat sources;

贮存于阴凉通风处，保质期 12 个月。Store in a cool and ventilated place with a shelf life of 12 months.

安全性 Safety：

操作时请戴防护器具，避免直接接触皮肤、眼睛或衣物，如不慎粘触，请以皂水清洗。详细说明请参阅【物质安全资料表】Wear protective equipment during operation to avoid direct contact with skin, eyes or clothing. Wash with soapy water if sticky. Please refer to [MSDS]

说明：以上数据仅供参考，其真实性和完整性以实际产品值为准。 Note: the above data is for reference only, its authenticity and integrity are based on the actual product value.

官网：www.sunb88.com

买化塑 智慧商铺：