



ADH937 产品说明书

Technical Data Sheet

2021 版

产品名称 Product Name: 附着力聚酯
Adhesive polyester

产品代号 Product Code: ADH937

性能指标: Performance indicators:

外观 Appearance (25℃):	粘稠透明液体 viscous transparent liquid
色数 Chromatic number (Fe-Co):	≤1#
粘度 Viscosity:	450-2500 cps (25℃)
官能度 Functional:	2
固含 Solid content:	≥98%
酸价 Acid value	<8
包装规格 Packing:	20kg/200kg

特性 Features:

- 对三聚氰胺板、玻璃、陶瓷、金属等基材附着力好;
Good adhesion to melamine plate, glass, ceramics, metals and other substrates;
- 与基材剥离强度高; High peeling strength with substrate;
- 表面硬度高, 固化收缩率低; High surface hardness, low curing shrinkage;
- 抗黄变性能优异。Excellent yellowing resistance.

用途 Application:

主要用于三聚氰胺板覆膜 UV 面漆。Mainly used for melamine plate coating UV topcoat.
免底漆三聚氰胺板覆膜 UV 面漆参考配方: reference formula for UV topcoat without primer melamine plate:
ADH937-----10,
PUA2296 2 Functional polyurethane-----4,
PUA2630 6 Functional polyurethane-----3,
1173-----1.

贮存 Storage:

本品须远离阳光及热源; This product should be away from sunlight and heat sources;
贮存于阴凉通风处, 保质期 12 个月。Store in a cool and ventilated place with a shelf life of 12 months.

安全性 Safety:

操作时请戴防护器具, 避免直接接触皮肤、眼睛或衣物, 如不慎粘触, 请以皂水清洗。详细说明请参阅【物质安全资料表】
Wear protective equipment during operation to avoid direct contact with skin, eyes or clothing. Wash with soapy water if sticky. Please refer to [MSDS]

说明: 以上数据仅供参考, 其真实性和完整性以实际产品值为准。 Note: the above data is for reference only, its authenticity and integrity are based on the actual product value.

销售商: 广东顺德本诺新材料有限公司
Vendors: Guangdong Shunde Bennuo New Material Co. Ltd
电话 Tel: 0757-22812771; 传真 Fax: 0757-23275835; 邮编 Zip: 528311

生产商: 南雄市三本化学科技有限公司
Manufacturer: Nanxiong Sanben Chemical Technology Co., Ltd
电话 Tel: 0751-6925031; 传真 Fax: 0751-6925032; 邮编 Zip: 512400

地址: 广东省佛山市顺德区北滘新城区怡和中心 601.
Address: 601 Yihe Center, Beijiao Xincheng District, Shunde District, Foshan City, Guangdong Province .

地址: 广东省韶关南雄市珠玑工业园平安一路 7 号
Address: No.7 Ping An Road, Zhuji Industrial Park, Nanxiong City, Shaoguan City, Guangdong Province

