

DESCRIPTION AND KEY PERFORMANCE PROPERTIES / 概述

S-101
是一款阴离子型亲水改性的多异氰酸酯预聚体，水分散性好，环保无溶剂，100%固含量。与水性羟基树脂配套用于双组份聚氨酯涂料，漆膜具有高光泽、高丰满度、抗黄变、并具有优异的耐化性和机械性能。

SALES SPECIFICATIONS/技术指标

Appearance /外观	透明粘稠液体	Particle Charge /离子类型	阴离子
Solids Content /固含,%	100		
Viscosity /粘度,cps/25°C	2000-3000		
NCO 含量,%	21.3±0.5		

TYPICAL CHARACTERISTICS / 特点

- 优异的耐水性，耐化性，机械性能
- 低粘度
- 高光泽、高丰满度，耐黄变性好
- 零 VOC

OPERATION INSTRUCTION / 使用说明

- 可使用氨基酯级溶剂 PMA（丙二醇甲醚醋酸酯），PGDA（丙二醇二醋酸酯）等开稀使用
- 需要稀释储存时，溶剂不能含羟基且需要氨基酯级，需要加 0.2-0.5%脱水剂

PACKING AND SAVE / 包装与储存

- 20KG 铁桶、220KG 铁桶
- 储存 5-30° C 环境下，储存期半年
- 取用后注意密封
- 高温或长时间接触空气会缩短保质期

The information contained in this document is based on trials carried out by our Technical centers and data selected from literature, but shall in no event be held or constitute or imply any warranty or undertaking, expressed or implied, or commitment on our part. Our formal specifications define the limit of our commitment. No liability whatever can be accepted by Copolymerline with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.

武汉仕全兴水性新材料有限公司

<http://www.shiquanxing.com>

地址：武汉市东西湖区八方路 8 号，电话 027-83267884，传真号码：027-83262285