

Amalchem

# AM718A

## 聚氨酯丙烯酸酯

### POLYURETHANE ACRYLATE



#### 产品介绍

PRODUCT INTRODUCTION

该产品为聚氨酯改性丙烯酸酯,具有低收缩、耐黄变、对各种金属、玻璃及塑料有良好的附着力,可广泛用于各种金属、玻璃、PC、ABS等各种基材的涂装及LEDUV固化的油墨。  
This product is a polyurethane modified acrylic ester with low shrinkage, resistance to yellowing, and good adhesion to various metals, glass, and plastics.

#### 应用特性

PRODUCT CHARACTERISTICS

对金属、玻璃及塑料等基材具有良好的附着力;LED-UV固化速度好;漆膜韧性好;固含量高;气味低。  
GOOD ADHESION TO SUBSTRATES SUCH AS METAL, GLASS, AND PLASTIC; GOOD LED-UV CURING SPEED; THE PAINT FILM HAS GOOD TOUGHNESS; HIGH SOLID CONTENT; LOW ODOR.

#### 应用领域

APPLICATION AREA



UV涂料  
UV COATING



LED油墨  
LED INK



真空电镀底油  
VACUUM ELECTROPLATING BASE OIL

#### 产品指标

PRODUCT CHARACTERISTICS

项目 PROJECT	指标 INDEX	检测标准 TESTING STANDARDS
外观 APPEARANCE	微黄/无色透明 TINY YELLOW/COLORLESS TRANSPARENT	目测 VISUALIZATION
有效成分 ACTIVE INGREDIENT	100%	理论值 THEORETICAL
NCO%	≤0.1	GB 12009.4-89
粘度MPA.S/60°C VISCOSITYMPA.S/60°C	10000-20000	GB/T 2794-2013
官能度 FUNCTIONALITY	2	理论值 THEORETICAL

地址:广东省英德市东华镇清远华侨工业区瀚和三路 电话:0763-3166358/3166359  
ADDRESS: Hanhe 3rd Road, Qingyuan Overseas Chinese Industrial Zone, Donghua Town, Yingde City, Guangdong Province