

Amalchem

# AM6205

## 改性环氧丙烯酸酯

### MODIFIED EPOXY ACRYLATE



#### 产品介绍

PRODUCT INTRODUCTION

在标准环氧的基础上,引入特殊的官能团,经合成反应而得,使之性能得到改良,具有更好的耐黄变、更高的丰满度、更快的固化速率和更低的收缩。

On the basis of standard epoxy, special functional groups are introduced and synthesized to improve its performance, with better yellowing resistance, higher fullness, faster curing rate, and lower shrinkage.

#### 应用特性

PRODUCT CHARACTERISTICS

优异的耐黄变性、韧性、固化速度快、高丰满度和低收缩率

EXCELLENT YELLOWING RESISTANCE, TOUGHNESS, FAST CURING SPEED, HIGH FULLNESS, AND LOW SHRINKAGE.

#### 应用领域

APPLICATION AREA



真空电镀  
VACUUM PLATING



塑料涂料  
PLASTIC COATING



印刷油墨  
PRINTING INK

#### 产品指标

PRODUCT CHARACTERISTICS

项目 PROJECT	指标 INDEX	检测标准 TESTING STANDARDS
外观 APPEARANCE	微黄透明 SLIGHTLY YELLOW TRANSPARENT	目测 VISUALIZATION
酸值 (mg KOH/g) ACID VALUE (mg KOH/g)	≤5.0	GB/T 6743-2008
有效成分	100%	理论值 THEORETICAL
粘度 MPA.S/25°C VISCOSITY MPA.S/25°C	40000-80000	GB/T 2794-2013
官能度 FUNCTIONALITY	2	理论值 THEORETICAL

地址:广东省英德市东华镇清远华侨工业区瀚和三路 电话:0763-3166358/3166359

ADDRESS: Hanhe 3rd Road, Qingyuan Overseas Chinese Industrial Zone, Donghua Town, Yingde City, Guangdong Province