

Amalchem

# AM3201D

## 聚酯丙烯酸酯

### POLYESTER ACRYLATE



#### 产品介绍

PRODUCT INTRODUCTION

该辐射固化树脂是由特殊丙烯酸单体聚合而成的低分子量齐聚物，对颜料、哑粉有较好的润湿性，丰满度高，产品粘度低。  
This radiation cured resin is a low molecular weight oligomer polymerized from special acrylic monomers, which has good wettability to pigments and powders, high fullness, and low product viscosity.

#### 应用特性

PRODUCT CHARACTERISTICS

润湿性好、低粘度、丰满度高、高反应活性，涂膜柔韧性好。  
GOOD WETTABILITY, LOW VISCOSITY, HIGH FULLNESS, HIGH REACTIVITY, AND GOOD FLEXIBILITY OF THE COATING FILM.

#### 应用领域


APPLICATION AREA



木器涂料  
WOOD COATINGS



木地板涂料  
WOOD FLOOR COATING



PVC地板涂料  
PVC FLOOR COATING



真空电镀  
VACUUM PLATING



塑料涂料  
PLASTIC COATING



印刷油墨  
PRINTING INK

#### 产品指标

PRODUCT CHARACTERISTICS

项目 PROJECT	指标 INDEX	检测标准 TESTING STANDARDS
外观 APPEARANCE	微黄透明 SLIGHTLY YELLOW TRANSPARENT	目测 VISUALIZATION
有效成分 ACTIVE INGREDIENT	100%	理论值 THEORETICAL
酸值 (MG KOH/G) ACID VALUE (MG KOH/G)	≤3.0	GB/T 6743-2008
粘度 MPA.S/25°C VISCOSITY MPA.S/25°C	80-150	GB/T 2794-2013
官能度 FUNCTIONALITY	2	理论值 THEORETICAL

地址: 广东省英德市东华镇清远华侨工业区和三路 电话: 0763-3166358/3166359

ADDRESS: Hanhe 3rd Road, Qingyuan Overseas Chinese Industrial Zone, Donghua Town, Yingde City, Guangdong Province