

Amalchem

AM2311

UV哑光树脂

UV MATTE RESIN



产品介绍

PRODUCT INTRODUCTION

该哑光树脂是三官聚氨酯丙烯酸酯，具有自消光、固化速度快、耐黄变、极佳的手感，与树脂相容性佳，可与任意比例树脂调节漆膜光泽，作为光固化涂料的哑光剂使用。

This matte resin is a trifunctional polyurethane acrylate with self extinction, fast curing speed, resistance to yellowing, excellent hand feel, and good compatibility with the resin. It can be used as a matte agent for light curing coatings by adjusting the gloss of the paint film with any proportion of resin.

应用特性

PRODUCT CHARACTERISTICS

比AM2310硬度高、自消光、耐黄变、手感佳、固化速度快、粘度低。


COMPARED TO AM2310, IT HAS HIGHER HARDNESS, SELF EXTINCTION, RESISTANCE TO YELLOWING, GOOD HAND FEEL, FAST CURING SPEED, AND LOW VISCOSITY.

应用领域

APPLICATION AREA



木器涂料
WOOD COATINGS



木地板涂料
WOOD FLOOR COATING



印刷油墨
PRINTING INK

产品指标

PRODUCT CHARACTERISTICS

项目 PROJECT	指标 INDEX	检测标准 TESTING STANDARDS
外观 APPEARANCE	微黄/无色透明 TINY YELLOW/COLORLESS TRANSPARENT	目测 VISUALIZATION
有效成分 ACTIVE INGREDIENT	100%	理论值 THEORETICAL
粘度 MPA.S/25°C VISCOSITY MPA.S/25°C	80-400	GB/T 2794-2013
官能度 FUNCTIONALITY	3	理论值 THEORETICAL

地址：广东省英德市东华镇清远华侨工业区瀚和三路 电话：0763-3166358/3166359

ADDRESS: Hanhe 3rd Road, Qingyuan Overseas Chinese Industrial Zone, Donghua Town, Yingde City, Guangdong Province