

水性乳液：建筑涂料，工业漆

产品代码 Product Code	聚合物类型 Polymer Type	固含量 (%) Solid Content	布氏粘度 Brookfield Viscosity	pH at 25°C	粒径 (微米) Average Particle Size (um)	Tg (°C)	MFFT (°C)	特点 Benefits	主要应用 Main Applications
5166T	苯丙共聚乳液 Styrene acrylate Copolymer emulsion	47±1	1000-4000 (4#.60rpm, 25°C)	7.0-9.0	0.1-0.2	+24	18	①附着力强 ②优异的耐擦洗性 ③耐水耐碱 ④相容性好 ①Good fastness ②Excellent scrub resistance ③Good resistance to water & alkali ④Good compatibility	●内外墙乳胶漆 ●Latex paint
5312	苯丙共聚乳液 Styrene acrylate Copolymer emulsion	50±1	400-1600 (3#.60rpm, 25°C)	8.0-9.0	0.2-0.4	-8	<0	①优异的水泥相容性 ②优异的柔韧性 ③优异的低温性能 ④耐水耐碱 ①Excellent cement compatibility ②Excellent flexibility ③Excellent performance in low temperature ④Good resistance to water & alkali	●水泥基防水涂料 ●Cement waterproof coating