

易施宝系列

EASY CONSTRUCTION

产品特性

- 操作简单，能很有效地填充木眼，防止下陷。
- 突出木纹纹理，增强纹理立体色感。
- 提升效率，节省工时。

施工说明

- 平面可采用刮刀刮涂，不适用铁制刮刀，请选择橡胶或塑胶刮板(刀)
- 线条位置可采用刷涂，主剂可用PU稀释剂调稀后再刷，并做到用碎布清理干净，只留木眼，不留木径。
- 雕花部位可采用擦涂，并做到用碎布清理干净，只留木眼，不留木径。
- 以上也均可采用擦涂完成。
- 如需对颜色进行调整，请使用格丽斯色浆或色精进行调色，但不宜超过主剂的5%。
- 待干30分钟以后可直接喷涂PU头度底漆。

注意事项

- 残留在木径上的易施宝必须清理干净，做到只留木眼，不留木径。
- 残留在沟槽或异形件较深部分必须清理干净，可使用自制竹片清理。
- 开罐后，表层多余部分油脂不适合使用，将影响层间附着力。
- 软木、浅木眼木材(如松木、杉木等)、实木等板材禁用。
- 严禁做完易施宝之后直接使用PE底漆。
- 冒胶严重及不了解的板材，一定要先期做小板附着力的测试。

包装规格

- 25kg / 4kg

PRODUCT CHARACTERISTICS

- High gloss and transparency, unique, excellent weather ability and fastness.
- And all kinds of resins have good solubility, good solubility, but also the use of low toxic alcohol solvent.
- More liquid products, more convenient to use.

THE CONSTRUCTION OF THE SPECIFICATIONS

- The plane can be scraper scraper, not suitable for iron scraper, please choose the rubber or plastic scraper (knife);
- The line position can be applied by brush, the main agent (FL00X) with PU diluent dilute brush again, and do clean up with a rag, leaving only the wooden eye, leaving no wood diameter;
- The site can be carved rubbing, and be clean with a rag, leaving only the wooden eye, leaving no wood diameter;
- The above can also be used brush to finish;
- If you want to adjust the color, please use Glaze for color, but not more than 5% of the main agent;
- To be dry after 30 minutes can be directly painted PU head primer.

MATTERS NEEDING ATTENTION

- Residual in the wood on the easy to treasure must be clean, so that only stay wood, do not stay wood path;
- Remaining in the deep part of the groove or alien part must be cleaned and can be cleaned with homemade bamboo;
- After opening the tank, the excess part of the surface grease is not suitable for use, will affect the adhesion between the layers;
- Cork, light wood wood (such as pine, fir, etc.), solid wood and other sheet banned;
- It is strictly forbidden to use pe primer directly after easy construction
- Take the rubber serious and do not understand the plate, we must first do small board adhesion test;

PACKING SPECIFICATION

- 25kg / 4kg

产品介绍 PRODUCT INTRODUCTION

产品编号 Product No.	产品名称 Product name	规格 Specifications	性能特点 properties
YSB-700B	透明省漆易施宝 Transparent provincial paint yishibao	20Kg	具有更佳的附着力，展色性好，颜色通透，有一定的填充性，可加格丽斯色浆和色精调色，施工简单方便 It has better adhesion, good color development, transparent color and certain filling ability. It can be mixed with Grice color paste and color essence, and the construction is simple and convenient.
YSB-700	透明省漆易施宝（高粘） Transparent paint saving and easy to apply (high viscosity)	25Kg	可以在白坯上擦涂、干速快、颜色层次感强，可加1-3%高浓度色精调色，也可加5-10%的格丽斯色浆调色，可以直接喷涂PU底、NC底，不建议直接喷PE底 It can be rubbed on the blank with fast drying speed and strong sense of color hierarchy. It can be toned with 1-3% high concentration color essence or 5-10% Grice color paste. It can be directly sprayed with PU bottom and NC bottom. It is not recommended to spray PE bottom directly.
YSB-700A	透明省漆易施宝（低粘） Transparent paint saving and easy to apply (low viscosity)	24Kg	可以在白坯上擦涂、干速快、颜色层次感强，可加1-3%高浓度色精调色，也可加5-10%的格丽斯色浆调色，可以直接喷涂PU底、NC底，不建议直接喷PE底 It can be rubbed on the blank with fast drying speed and strong sense of color hierarchy. It can be toned with 1-3% high concentration color essence or 5-10% Grice color paste. It can be directly sprayed with PU bottom and NC bottom. It is not recommended to spray PE bottom directly.
YSB-701	透明省漆易施宝 Transparent provincial paint yishibao	20Kg	附着力好、着色好、擦涂后可直接喷涂PE底或辊涂喷涂UV底漆，加色精调色，色精量不超过3% After good adhesion, good coloring and rubbing, directly spray PE bottom or roll spray UV primer, add color essence and color matching, and the color essence shall not exceed 3%

施工工艺 CONSTRUCTION TECHNOLOGY

YSB-701B易施宝使用案例 YSB-701B use case of yishibao

工序 procedure	材料品牌编号名称 Material brand no. Name	施工方法详细说明 Construction method	施工要点 Main points of construction
白坯处理 Blank treatment	贴木皮或实木如橡木或黑胡桃 A veneer or solid wood, such as oak or black walnut.	清洗胶渍等 Cleaning glue stains, etc.	保证工件表面干净，无污渍 Ensure the surface of the workpiece is clean and free of stains
打磨 Polish	320#砂纸 320# sandpaper	手磨或机磨 Hand or machine grinding	去毛刺，木刺，去污渍、顺木纹打磨平整、光滑 Deburring, wood pricking, stain removal, and wood grain polishing are smooth and smooth.
YSB-701	加色精调成黑胡桃底色 Add color essence to black walnut background	擦涂 Rubbing	均匀擦涂，再用棉布顺木纹收干净，做到基本不残留 Wipe evenly, and then use cotton cloth to clean along the wood grain, so that there is no residue.
PE底漆 PE primer	喷涂，也可UV底漆 Spray or UV primer	喷涂 Spray	均匀喷涂两个“+”字 Spray two "+" words evenly
打磨 Polish	砂纸320# 320# sandpaper	手磨 Hand grinding	顺木纹打磨，轻砂 Polish along wood grain, light sand
PE底漆 PE primer	喷涂，也可UV底漆 Spray or UV primer	喷涂 Spray	均匀喷涂两个“+”字 Spray two "+" words evenly
打磨 Polish	砂纸320#、600# 320# 600# sandpaper	手磨 Hand grinding	顺木纹打磨，轻砂 Polish along wood grain, light sand
修色 Color fixing	修色油加色精 Toner oil and toner	修色 Color fixing	均匀修到样板颜色 Even trim to sample color
轻砂 Light sand	600#、1000#	轻磨 Light grinding	去除表层颗粒杂质 Remove surface particle impurities
罩光 Cover light	清面漆 Finish coat	喷涂 Spray	喷涂面漆两个“+”字，24小时后包装 Spray two "+" words on the top coat, 24 hours later
工艺特性：可直接喷PE底漆或UV底漆，也具有很好的附着力 Process characteristics: can spray PE primer or UV primer directly, also has good adhesion			