温馨提示

尊敬的客户：
请仔细审核并确认图案颜色，文字，尺寸及排版方向。本公司将根据你的确认文件进行制版，
按确认文件制版后若发生一切纠纷，本公司概不负责。

黑 专兰 兰 红 黄 白 白 胶

桶型：20L-2蓝桶

颜色与专兰统一

白字加专兰描边

950 mm

浅红底代表透明

图案尺寸：902.2mmX256mm

普乐真石漆 NATYRAL STONE PAINT

普乐真石漆是一种由水性丙烯酸乳液，彩砂，助剂等调制而成的仿石、仿岩效果的水性艺术涂料。设计方便，无缝施工，适合各种面积大小，对复杂造型特别能显示优越性。具有高耐候性、耐热、耐水、抗酸碱、不褪色、耐老化等特点，长时间保护建筑的美观。可适用于建筑物的外墙饰面及具有建筑物改造。

Natural stone paint is an acrylic composite emulsion based water-born texture paint, which combined with color sand and additives to simulate stone and tile. Easy to design, seamless construction, suitable for all sizes, especially good for complex shapes. The product has attributes of high durable, heat and water resistant, acid and alkali resistant, colorfast, aging resistance. Protect the beauty of the building for a long time. It can be applied to the exterior and building renovation.

保质期 SHELF LIFE

必须存放于阴凉干燥的地方，严防霜冻（不低于0℃），此产品保质期12个月，生产日期请参照标签。（获得更详细的资料，请向本产品的经销商索取产品使用说明书）

Always store this product in a cool, dry place and avoid freezing (No less than 0℃). This product has a shelf life of 12 months. Please see manufacture date on the sticker.
（TO GET MORE INFORMATION ABOUT THIS PRODUCT, PLEASE REQUEST PRODUCT DATA SHEET FROM PRODUCT DEALER ）

基层处理 SURFACE PREPARATION

要上涂的表面要平整，全无油脂、尘污和松散物质。新抹灰的水泥墙应养护30天以上，墙体（或腻子）含水率必须小于10%，pH值必须低于10，使用配套曼得丽专业底漆。

Surfaces must be even, thoroughly clean, dry and free from all loose dirt, chalk or powder. New surfaces such as plaster and concrete should be fully dry before painting, with moisture content less than 10% and pH value below 10. Suitable MAIDENLY primers must be used.

产品执行标准 PRODUCT EXECUTION STANDARDS

JG/T 24-2018《合成树脂乳液砂壁状建筑涂料》，GB 24408-2009《建筑用外墙涂料中有害物质限量》

JG/T 24-2018 Sand textured building coating based on synthetic resin emulsion, GB 24408-2009 Limit of harmful substances of exterior wall coatings

施工 APPLICATION

可用钢制批刀，特殊喷枪等工具施工。具体的施工效果根据施工工具、施工方法而定。面涂于中层涂之间需间隔48小时以上，气温低或空气湿度较大时应适当延长。该产品无需稀释，切忌将已干结的料加入该料中搅拌用。喷涂时选择合适的压力进行，如有需要，还可在漆膜处于半干情况下进行细压以获得细平状的浮雕效果。喜欲温度低于5℃或环境湿度超过85%时请勿施工。用过的工具应立即用肥皂及温水清洗干净。不可重复使用接触过不同型号、不同性能漆料的器具。如有需要，应将其报废物清除干净并彻底洗净后才能使用。

正常情况下，理论涂布率平均为4.0-5.5公斤/平方米，实际涂布率取决于基材平整度，颜色，施工方法和对施工效果的要求。

This product is suitable for application by steel trowel, special spray. Different tools can provide different application effect. Recoat time Natural stone paint and topcoat is 48 hours. For spray application, proper spray pressure is required. Natural stone paint is a product which requires no thinning. Don't put dry and hard material into the normal paint to stir and use. Clean all equipment with soap and warm water immediately after use. Drums and application tools contaminated with this product shall not be reused for any other types of paint application. If there is a need, all paint contamination must be completely removed. Do not apply below 5℃ or if relative humidity above 85%. Avoid application under the bad weather.

Theoretically coverage which can be achieved under normal conditions is around 4.0-5.5 kg/㎡, Actual coverage is depending on substrate leveling, color and desire of application effect.

无信号词

根据最全球化学品统一分类和标签制度（GHS）未被分类为危害品。

一般防范说明：放在儿童伸手不及之处。如需医嘱，请将产品容器或标签拿给医生手边。

预防措施：避免接触眼睛、皮肤或衣服。

其它安全提示：对漆膜的处理例如打磨、如特等可能产生有害的粉尘或烟雾。工作场所要保持良好的通风。请使用合适的个人防护设备。

事故响应：如果感觉不适，立即就医。

储存要求：密封存放于阴凉干燥处，避免阳光直射。

废弃处置：废弃处置应遵守国家和地方的环保标准。

NO SIGNAL WORD

The product is NOT classified as hazardous according to China GHS regulations.

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Do not get in eyes, on skin, or on clothing.

Other safety tips : Film treatments such as sanding and burning may generate hazardous dust or fumes. Work in well ventilated areas. Use suitable personal protection equipment.

Response : Call a poison center or doctor if you feel unwell.

Storage : Store in a cool, dry place, away from direct sunlight.

Disposal : Disposal should comply with all local and national regulations.

浙江曼得丽涂料有限公司
ZJ MAIDENLY PAINT CO., LTD.
地址：浙江省海乡市塘甸工业园区天才路65号（314503）
Add：No.65 Tiancai Road, Tiedian Industrial Park, Tongxiang City, Zhejiang 314503 P. R. China
总机/Tel：+86-573-88867777 88861877 88862917
传真/Fax：+86-573-88867227 电邮/E-mail：customer@maidenly.com.cn
www.maidenly.com.cn 400 905 7321

使用前请阅读产品安全技术说明书。
化学事故应急咨询电话：0532-83889090
Please read the product safety date sheet before use.
Emergency number(24 hours)：0532-83889090

防止 保持干燥 产地储存 本向盒装 小心搬运

280 mm

桶高295mm，图高230mm，上下各空32.5mm，图案一圈包满空10mm